

Printed : 27/05/2020

Revised : V1-R-2-CLP from 27/05/2020

## LIMETTE DISTILLEE MEXIQUE H.E.

## 1. SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

### 1.1. Product identifier

Name of the substance/mixture : LIMETTE DISTILLEE MEXIQUE H.E.

N° CAS TSCA	: 8008-57-9
N° CE	: 290-010-3
N° index REACH An VI	:/
N° REACH (partially)	: Exempt

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use only

End use :

Fragrances / Cosmetic / Flavours

1.3. Details of the supplier of the safety data sheet

SAS PCW Aromagrasse - 45 bd Marcel Pagnol 06130 Grasse - FRANCE Tel : +33 (0)4 92 42 35 00 Fax : +33 (0)4 92 42 35 19 Web : www.pcwfrance.com Email : info@pcwfrance.com

Technical manager : regulatory@pcwfrance.com

## 1.4. Emergency telephone number

Emergency information service of the company

+33(6) 07 85 74 60 (24h/24h)

National emergency information service

INERIS : +33(8) 20 20 18 16

Anti poison Centers in France

ORFILA : +33(1) 45 42 59 59

## 2. SECTION 2 - HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification :



Printed : 27/05/2020 LIMETTE DISTILLEE MEXIQUE H.E.

(RegulationCLP)

Asp. Tox. 1Aspiration hazard 1Aquatic Acute 1Hazardous to the aquatic environment, acute hazard 1Aquatic Chronic 1Hazardous to the aquatic environment, long-trem hazard 1Flam. Liq. 3Flammable Liquids 3Skin Irrit. 2Skin corrosion / irritation 2Skin. Sens. 1Sensitisation skin 1

H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H410 - Very toxic to aquatic life with long lasting effects.

### 2.2. Label elements

GHS Classification :

(RegulationCLP)



Warning mention : Danger

- Asp. Tox. 1 Aspiration hazard 1
- Aquatic Acute 1 Hazardous to the aquatic environment, acute hazard 1

Aquatic Chronic 1 Hazardous to the aquatic environment, long-trem hazard 1

Flam. Liq. 3 Flammable Liquids 3

Skin Irrit. 2Skin corrosion / irritation 2Skin. Sens. 1Sensitisation skin 1

H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H410 - Very toxic to aquatic life with long lasting effects.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240+P241 - Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting/.../equipment.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P501 - Dispose of contents/container according to the local/ regional / national / international Regulation.

### 2.3. Other hazards

Revised : V1-R-2-CLP from 27/05/2020



Printed : 27/05/2020 LIMETTE DISTILLEE MEXIQUE H.E.

Revised : V1-R-2-CLP from 27/05/2020

### Contains Limonene, gamma-Terpinene, alpha-Pinene, Myrcene, Linalool

CMR (Reg. 1223/2009/EEC) : See certificate

## 3. SECTION 3 - COMPOSITION INFORMATION ON INGREDIENTS

### 3.1. Substances

Material	C.A.S	EINECS	Classification	Percent %
Limonene (Regist. : N° INDEX 601-029-00-7)	5989-27-5	227-813-5	Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1, Flam. Liq. 3, Skin Irrit. 2, Skin. Sens. 1B - H226, H304, H315, H317, H400, H410	> 50 %
alpha-Pinene (Regist. : /)	80-56-8	201-291-9	Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1, Flam. Liq. 3, Skin Irrit. 2, Skin. Sens. 1B - H226, H304, H315, H317, H400, H410	[ 10-20 ]
gamma-Terpinene (Regist. : /)	99-85-4	202-794-6	Asp. Tox. 1, Flam. Liq. 3 - H226, H304	[ 10-20 ]
Linalool (Regist. : N° INDEX 603-235-00-2)	78-70-6	201-134-4	Eye Irrit. 2, Skin Irrit. 2, Skin. Sens. 1B - H315, H317, H319	[ 1-5 ]
Myrcene	123-35-3	204-622-5	Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 2, Flam. Liq. 3, Skin Irrit. 2 - H226, H304, H315, H319, H400, H411	[ 1-5 ]
Citral (Regist. : N° INDEX 605-019-00-3)	5392-40-5	226-394-6	Skin Irrit. 2, Skin. Sens. 1B - H315, H317, H319	[0-1]
Citronellal (Regist. : /)	106-23-0	203-376-6	Eye Irrit. 2, Aquatic Chronic 3, Skin Irrit. 2, Skin. Sens. 1B - H313, H315, H317, H319, H412	[0-1]
Geraniol (Regist. : /)	106-24-1	203-377-1	Eye Dam. 1, Skin Irrit. 2, Skin. Sens. 1B - H315, H317, H318	[0-1]
Botanical name : Cit	rus aurantif	olia Chris	stman Swingle	
Description : Ess	sential oil ex	ctracted I	by distillation from the outer part	of fresh lime

### 3.2. Mixtures

NO CONCERNED

## 4. SECTION 4 - FIRST AID MEASURES

### 4.1. Description of first aid measures

General notes : Please refer to the risk and safety statements (section 2)

peel

**Following inhalation :** If inhaled : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Remove collar, belt, tie... Give artificial respiration if not breathing.

Following ingestion : If swallowed: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting.

Following skin contact : If on skin (or hair) or clothing rinse immediately contaminated clothing and skin with plenty of water

before removing clothes. If the symptom persists, consult a doctor.



Printed : 27/05/2020 LIMETTE DISTILLEE MEXIQUE H.E.

Revised : V1-R-2-CLP from 27/05/2020

**Following eye contact :** Rinse cautiously with water for several minutes (15 minutes open eyelids). Remove contact lenses, if present and easy to do. Continue rinsing. In case of disorder, consult an ophtalmologist.

Self-protection of the first aider : In lack of appropriate formation, none initiative should imply an individual risk.

## 4.2. Most important symptoms and effects, both acute and delayed

See section 2

## 4.3. Indication of any immediate medical attention and special treatment needed

See section 2

## 5. SECTION 5 - FIREFIGHTING MEASURES

### 5.1. Extinguishing media

**Suitable extinguishing media :** Use an extinguishing agent suitable for the surrounding fire. CO2, powder, foam, specific liquid.

Unsuitable extinguishing media : Never use a direct stream of water.

### 5.2. Special hazards arising from the substance or mixture

Flammability : The product is easily flammable.

Prevention : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Particular risks linked to exposure : see section 2

### Hazardous combustion products :

Release of poison gases : Monoxide de carbone (CO), Dioxyde de carbon (CO2), Oxyde d'azotes (NOx), Dioxyde de soufre (SO2), Cyanures (CN) ....

## 5.3. Advice for firefighters

**Fire-fighting equipment :** use an appropriate personal protective equipment with an approved positive-pressure self-contained breathing apparatus.

## 6. SECTION 6 - ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Call immediately the emergency personnel.

Promote adequate ventilation in the area.

For non-emergency personnel

Keep them away from the area. Avoid all sources of ignition (spark of flame). Avoid skin/eye contact. Do not inhal vapours.



Printed : 27/05/2020

LIMETTE DISTILLEE MEXIQUE H.E.

Revised : V1-R-2-CLP from 27/05/2020

For emergency responders

Use personal protective equipment. In case of accidental spills, wear protective gloves during the handling.

## 6.2. Environmental precautions

Avoid the dispersion and flow of the product. Keep away from drains, surface and ground water. Inform the competent authorities if the product enters in ground or surface waters.

### 6.3. Methods and material for containment and cleaning up

### For containment

The spillage is contained with sand or inert powder. The chemical waste is placed in sealed containers.

### For cleaning up

The soiled elements (rags, absorbent papiers, filters) are immediately soaked into water. The chemical waste are rapidly treated according to the local reglementation

Other informations Only qualified personnel is allowed to clean up.

### 6.4. Reference to other sections

See section 8 for personal protective equipment and section 13 for waste treatment.

## 7. SECTION 7 - HANDLING AND STORAGE

## 7.1. Precautions for safe handling

Protective measures: See section 2.2



Measures to prevent fire:

Do not smoke. Do not expose to excessive heat or ignition sources (spark or flame).

Measures to prevent aerosol and dust generation: Maintain adequate ventilation in the area.

Measures to protect the environment:

Avoid spreading product and keep it from spilling. Precautions or coming in contact with the ground, waterways, drains and vents.

Advice on general occupational hygiene: Follow the general hygiene rules.

### 7.2. Conditions for safe storage, including any incompatibilities



Printed : 27/05/2020 LIMETTE DISTILLEE MEXIQUE H.E.

Revised : V1-R-2-CLP from 27/05/2020

Storage conditions: Store in its original packaging in a cool dry place, away from light.

<u>Technical measures:</u> Close the container after use. In case of transferring, reproduce the labelling.

Packaging materials: Preserve only in the container of origin.

Respect the general rules of incompatibility.

Storage :

# Keep under Nitrogen, at cool temperature (max 18°C). Avoid prolonged exposure to light, humidity and air.

### 7.3. Specific end use(s)

Wash the hands and any other zone exposed with soap and water before eating, drinking, to smoke and before leaving work.

8. SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1. Control parameters

**Measures of technical order :** Avoid contact with eyes, skin and closes. Do not ingest. Do not inhal vapors. Use proper personal protective equipment.

**Monitoring procedures** : If the product contains ingredients presenting exposure limits, he can turn out necessary to make an examination followed by the persons, by the atmosphere in the workplace either bodies living to end the efficiency of the ventilation or the other control measures or estimate the need to use of the material of protection of respiratory tracts. It is important to put back you in the European standard EN 689 concerning the methods to estimate the exhibition by inhalation to the chemical agents and to the national general documents of politics relative to the methods to determine dangerous substances.

### 8.2. Exposure controls

#### Appropriate technical controls :

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure.

### Personal protection measures :

#### **Personal protection :**

-Protection des mains : Protection non requise.
-Protection respiratoire : En cas de ventilation insuffisante, porter un appareil respiratoire approprié.

**Respiratory protection**: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates that is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter apparatus (dust masks or half masks)

Type of filters

Type AX (Brown) : Organic compounds boiling point < 65°C

Type A (Brown) : Organic compounds boiling point > 65°C

- Type B (Grey) : Inorganic gasses and fumes.
- Type P (White) : Particles, dusts and aerosols

**Hand protection** : Impermeable and chemical resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary >8 hours before piercing : vinyle disposable.

**Remark** : Recommended impermeable goggles do not only depend of his matter. Other factors can have a signifiant effect on impermeability, like their thickness or specific use or temperature conditions. In all cases, matter certificates should be selected. Ask



Printed : 27/05/2020 LIMETTE DISTILLEE MEXIQUE H.E.

Revised : V1-R-2-CLP from 27/05/2020

your supply if the goggles are appropriate to this use.

**Eyes protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommanded : Splash googles, safety glasses with side-shields.

**Skin protection** :Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Body : Recommanded : lab coat (sarrau), general.

Type 3 : Liquid impermeability

Type 4 : Aerosol impermeability

Type 6 : Impermeability limited to liquid splashs

Foot : Recommanded : neoprene

Upper and sole resistant and impermeable (Hydrocarbure resistant).

## 9. SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Solubility ethanol :	Yes
Appearance :	Liquid
Color :	Colorless to very pale yellowish
Odour :	Lime note - very zesty
Density 20/20°C :	[0.844 ; 0.859]
Refractive index n (20/D) :	[1.468 ; 1.482]
Optical rotation (°) :	[+46.0 ; +61.0]
Peroxides value mmol/kg :	max. 20
Boiling point (°C) :	-
Flash point (°C) (close cup) :	49
Vapor pressure :	-

## 9.2. Other information

NO CONCERNED

10. SECTION 10 - STABILITY AND REACTIVITY

### 10.1. Reactivity

Avoid powerful oxidizing agents

### 10.2. Chemical stability

Stable under normal conditions.

Shelf life :

## 12 months, according to storage conditions

### 10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.



Printed : 27/05/2020 LIMETTE DISTILLEE MEXIQUE H.E.

Revised : V1-R-2-CLP from 27/05/2020

### 10.4. Conditions to avoid

Avoid any potential source of heat.

## 10.5. Incompatible materials

NO CONCERNED

### 10.6. Hazardous decomposition products

**Thermal decomposition** / **conditions to be avoided:**Avoid contact with any flame or spark, flame, Overheat.Avoid Direct rays of the sun. No decomposition if used according to specifications. **Dangerous decomposition products:** No dangerous decomposition products known.

## 11. SECTION 11 - TOXICOLOGICAL INFORMATION

11.1. Information on toxicological

Toxicity data :No dataLD50 oral (rat) :> 5000 mg/kgLD50 Dermal (rabbit) :No data

### 12. SECTION 12 - ECOLOGICAL INFORMATION

### 12.1. Toxicity

Do not leave the product, even diluted or in great quantity, penetrate the ground water, water or the drains.

LC50 Ecotoxicity :No dataEC50 Ecology :No data

12.2. Persistence and degradability

NO CONCERNED

12.3. Bioaccumulative potential

NO CONCERNED

12.4. Mobility in soil

÷

PNEC sol

12.5. Results of PBT and vPvB assessment

vPvB PBT

12.6. Other adverse effects

No data

13. SECTION 13 - DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods



Printed : 27/05/2020 LIMETTE DISTILLEE MEXIQUE H.E.

Revised : V1-R-2-CLP from 27/05/2020

**Product :** Does not have to be evacuated with the refuse. Not let it penetrate in the sewers. **Not cleaned packing :** Evacuation according to local reglementation.

## 14. SECTION 14 - TRANSPORT INFORMATION

ADR:



IMDG:



IATA:



14.1. UN number

ADR : 1169 ( Tunnel code (D/E) ) IMDG:1169 IATA :1169

### 14.2. UN proper shipping name

ADR : EXTRACTS, AROMATIC, LIQUID IMDG:EXTRACTS, AROMATIC, LIQUID IATA :EXTRACTS, AROMATIC, LIQUID

### 14.3. Transport hazard class(es)

ADR : 3 IMDG:3 IATA :3

14.4. Packing group

adr : III Imdg:III Iata :III

## 14.5. Environmental hazards

IMDG :

14.6. Special precautions for user

NO CONCERNED

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code



Printed : 27/05/2020

LIMETTE DISTILLEE MEXIQUE H.E.

Revised : V1-R-2-CLP from 27/05/2020

(Except particular case)

IBC Liquid substances Metal (31A, 31B, 31N) Plastic (31H1, 31H2)

<u>GRV Solid substances</u> Metal (11A, 11B, 21A, 21N) Plastic (11H1, 11H2, 21H1, 21H2)

## 15. SECTION 15 - REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Monographie (s) du RIFM n° : 170-G2.12

Custom tariff : **3301 19 20 00** 

15.2. Chemical safety assessment

## 16. SECTION 16 - OTHER INFORMATIONS

### Full H sentenses text in point 3 :

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Key literature ref	ferences and sources for data
Sources for data :	
Literature referen	
Literature referen	Ices EU : Reg. 1272/2008

Safety data sheet according to REG. 1272/2008/CE and its amendings These indications are founded on the current state of our knowledge, but do not constitute a guarantee as for the properties of the product and do not give place to a contractual legal report.

Modified points : 2.2 2.3 3.1 7.1 16