



Safety Data Sheet

Printed : 25/01/2021

Revised : V1-R-MP-2-CLP from 25/01/2021

YUZU TYPE

1. SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

1.1. Product identifier

Name of the substance/mixture : **YUZU TYPE**

N° CAS TSCA : **94266-47-4**

N° CE : **304-454-3**

N° index REACH An VI : /

N° REACH (partially) : **Exempt <1T**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : **Industrial use only**

End use : **Fragrances / Cosmetic / Flavours**

1.3. Details of the supplier of the safety data sheet

SAS PCW
Aromagrassse - 45 bd Marcel Pagnol
06130 Grasse - FRANCE
Tel : +33 (0)4 92 42 35 00
Fax : +33 (0)4 92 42 35 19
Web : www.pcwfrance.com
Email : info@pcwfrance.com

Technical manager : regulatory@pcwfrance.com

1.4. Emergency telephone number

Emergency information service of the company

+33(6) 07 85 74 60 (24h/24h)

National emergency information service

INERIS : +33(8) 20 20 18 16

Anti poison Centers in France

ORFILA : +33(1) 45 42 59 59

2. SECTION 2 - HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification :

Safety Data Sheet

Printed : 25/01/2021

YUZU TYPE

Revised : V1-R-MP-2-CLP from 25/01/2021

(RegulationCLP)


Asp. Tox. 1 Aspiration hazard 1
Aquatic Acute 1 Hazardous to the aquatic environment, acute hazard 1
Aquatic Chronic 1 Hazardous to the aquatic environment, long-term hazard 1
Flam. Liq. 3 Flammable Liquids 3
Skin Irrit. 2 Skin corrosion / irritation 2
Skin. Sens. 1 Sensitisation skin 1

H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H410 - Very toxic to aquatic life with long lasting effects.

2.2. Label elements

GHS Classification :

(RegulationCLP)



Warning mention : Danger

Asp. Tox. 1 Aspiration hazard 1
Aquatic Acute 1 Hazardous to the aquatic environment, acute hazard 1
Aquatic Chronic 1 Hazardous to the aquatic environment, long-term hazard 1
Flam. Liq. 3 Flammable Liquids 3
Skin Irrit. 2 Skin corrosion / irritation 2
Skin. Sens. 1 Sensitisation skin 1

H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H410 - Very toxic to aquatic life with long lasting effects.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240+P241 - Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/.../equipment.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P501 - Dispose of contents/container according to the local/ regional / national / international Regulation.

2.3. Other hazards

Contains Limonene, Linalool, Myrcene

Safety Data Sheet

Printed : 25/01/2021

YUZU TYPE

Revised : V1-R-MP-2-CLP from 25/01/2021

CMR (Reg. 1223/2009/EEC) :

See certificate

3. SECTION 3 - COMPOSITION INFORMATION ON INGREDIENTS

3.1. Substances

Material	C.A.S	EINECS	Classification	Percent %
Limonene (Regist. : N° INDEX 601-029-00-7)	5989-27-5	227-813-5	Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1, Flam. Liq. 3, Skin Irrit. 2, Skin. Sens. 1B - H226, H304, H315, H317, H400, H410	> 50 %
Linalool (Regist. : N° INDEX 603-235-00-2)	78-70-6	201-134-4	Eye Irrit. 2, Skin Irrit. 2, Skin. Sens. 1B - H315, H317, H319	[1-5]
Myrcene	123-35-3	204-622-5	Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 2, Flam. Liq. 3, Skin Irrit. 2 - H226, H304, H315, H319, H400, H411	[1-5]
Citral (Regist. : N° INDEX 605-019-00-3)	5392-40-5	226-394-6	Skin Irrit. 2, Skin. Sens. 1B - H315, H317, H319	[0-1]
Citronellal (Regist. : /)	106-23-0	203-376-6	Eye Irrit. 2, Aquatic Chronic 3, Skin Irrit. 2, Skin. Sens. 1B - H313, H315, H317, H319, H412	[0-1]
Citronellol (Regist. : /)	106-22-9	203-375-0	Skin Irrit. 2, Skin. Sens. 1B - H315	[0-1]
Geraniol (Regist. : /)	106-24-1	203-377-1	Eye Dam. 1, Skin Irrit. 2, Skin. Sens. 1B - H315, H317, H318	[0-1]
Terpinolene (Regist. : /)	586-62-9	209-578-0	Asp. Tox. 1, Aquatic Acute 1, Aquatic Chronic 1, Skin. Sens. 1B - H304, H317, H400, H410	[0-1]

Botanical name :

Citrus spp., Rutaceae

Description :

Citrus Species Peel Oil Expressed is an essential oil expressed from the epicarps of different Citrus spp., Rutaceae

3.2. Mixtures

NO CONCERNED

4. SECTION 4 - FIRST AID MEASURES

4.1. Description of first aid measures

General notes : Please refer to the risk and safety statements (section 2)

Following inhalation : If inhaled : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Remove collar, belt, tie... Give artificial respiration if not breathing.

Following ingestion : If swallowed: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting.

Following skin contact : If on skin (or hair) or clothing rinse immediately contaminated clothing and skin with plenty of water before removing clothes. If the symptom persists, consult a doctor.

Following eye contact : Rinse cautiously with water for several minutes (15 minutes open eyelids). Remove contact lenses, if present and easy to do. Continue rinsing. In case of disorder, consult an ophthalmologist.

Safety Data Sheet

Printed : 25/01/2021

YUZU TYPE

Revised : V1-R-MP-2-CLP from 25/01/2021

Self-protection of the first aider : In lack of appropriate formation, none initiative should imply an individual risk.

4.2. Most important symptoms and effects, both acute and delayed

See section 2

4.3. Indication of any immediate medical attention and special treatment needed

See section 2

5. SECTION 5 - FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire. CO₂, powder, foam, specific liquid.

Unsuitable extinguishing media : Never use a direct stream of water.

5.2. Special hazards arising from the substance or mixture

Flammability : The product is not flammable.

Prevention : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Particular risks linked to exposure : see section 2

Hazardous combustion products :

Release of poison gases : Monoxide de carbone (CO), Dioxyde de carbon (CO₂), Oxyde d'azotes (NO_x), Dioxyde de soufre (SO₂), Cyanures (CN)

5.3. Advice for firefighters

Fire-fighting equipment : use an appropriate personal protective equipment with an approved positive-pressure self-contained breathing apparatus.

6. SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Call immediately the emergency personnel.

Promote adequate ventilation in the area.

For non-emergency personnel

Keep them away from the area. Avoid all sources of ignition (spark of flame).
Avoid skin/eye contact. Do not inhal vapours.

For emergency responders

Safety Data Sheet

Printed : 25/01/2021

YUZU TYPE

Revised : V1-R-MP-2-CLP from 25/01/2021

Use personal protective equipment. In case of accidental spills, wear protective gloves during the handling.

6.2. Environmental precautions

Avoid the dispersion and flow of the product. Keep away from drains, surface and ground water. Inform the competent authorities if the product enters in ground or surface waters.

6.3. Methods and material for containment and cleaning up

For containment

The spillage is contained with sand or inert powder. The chemical waste is placed in sealed containers.

For cleaning up

The soiled elements (rags, absorbent papers, filters) are immediately soaked into water. The chemical waste are rapidly treated according to the local relementation

Other informations

Only qualified personnel is allowed to clean up.

6.4. Reference to other sections

See section 8 for personal protective equipment and section 13 for waste treatment.

7. SECTION 7 - HANDLING AND STORAGE

7.1. Precautions for safe handling

Protective measures:

See section 2.2



Measures to prevent fire:

Do not smoke. Do not expose to excessive heat or ignition sources (spark or flame).

Measures to prevent aerosol and dust generation:

Maintain adequate ventilation in the area.

Measures to protect the environment:

Avoid spreading product and keep it from spilling. Precautions or coming in contact with the ground, waterways, drains and vents.

Advice on general occupational hygiene:

Follow the general hygiene rules.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in its original packaging in a cool dry place, away from light.

Safety Data Sheet

Printed : 25/01/2021

YUZU TYPE

Revised : V1-R-MP-2-CLP from 25/01/2021

Technical measures: Close the container after use.
In case of transferring, reproduce the labelling.

Packaging materials: Preserve only in the container of origin.

Respect the general rules of incompatibility.

Storage : **Store in cool place (10°C max.), in tightly sealed original container.
Avoid prolonged exposure to light, heat and air.**

7.3. Specific end use(s)

Wash the hands and any other zone exposed with soap and water before eating, drinking, to smoke and before leaving work.

8. SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Measures of technical order : Avoid contact with eyes, skin and clothes. Do not ingest. Do not inhale vapors. Use proper personal protective equipment.

Monitoring procedures : If the product contains ingredients presenting exposure limits, it can turn out necessary to make an examination followed by the persons, by the atmosphere in the workplace either bodies living to end the efficiency of the ventilation or the other control measures or estimate the need to use of the material of protection of respiratory tracts. It is important to put back you in the European standard EN 689 concerning the methods to estimate the exhibition by inhalation to the chemical agents and to the national general documents of politics relative to the methods to determine dangerous substances.

8.2. Exposure controls

Appropriate technical controls :

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure.

Personal protection measures :

Personal protection :

-Protection des mains : Protection non requise.-Protection des yeux : Protection non requise.

-Protection respiratoire : En cas de ventilation insuffisante, porter un appareil respiratoire approprié.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates that is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter apparatus (dust masks or half masks)

Type of filters

Type AX (Brown) : Organic compounds boiling point < 65°C

Type A (Brown) : Organic compounds boiling point > 65°C

Type B (Grey) : Inorganic gasses and fumes.

Type P (White) : Particles, dusts and aerosols

Hand protection : Impermeable and chemical resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary >8 hours before piercing : vinyle disposable.

Remark : Recommended impermeable goggles do not only depend of his matter. Other factors can have a significant effect on impermeability, like their thickness or specific use or temperature conditions. In all cases, matter certificates should be selected. Ask your supply if the goggles are appropriate to this use.

Safety Data Sheet

Printed : 25/01/2021

YUZU TYPE

Revised : V1-R-MP-2-CLP from 25/01/2021

Eyes protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Recommended : Splash goggles, safety glasses with side-shields.

Skin protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Body : Recommended : lab coat (sarrau), general.

Type 3 : Liquid impermeability

Type 4 : Aerosol impermeability

Type 6 : Impermeability limited to liquid splashes

Foot : Recommended : neoprene

Upper and sole resistant and impermeable (Hydrocarbure resistant).

9. SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Solubility ethanol :	Yes
Optical rotation (°) :	[+71.00 ; +91.00]
Boiling point (°C) :	-
Flash point (°C) (close cup) :	48
Peroxides value mmol/kg :	[0 ; 20]
Refractive index n (20/D) :	[1.470 ; 1.480]
Odour :	Citrusy, almost floral, bitter, sweet, fresh
Color :	Colorless to yellow
Appearance :	Liquid
Densité à 20/4°C :	[0.845 ; 0.860]

9.2. Other information

NO CONCERNED

10. SECTION 10 - STABILITY AND REACTIVITY

10.1. Reactivity

Avoid powerful oxidizing agents

10.2. Chemical stability

Stable under normal conditions.

Shelf life : **12 months, according to storage conditions**

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

Safety Data Sheet

Printed : 25/01/2021

YUZU TYPE

Revised : V1-R-MP-2-CLP from 25/01/2021

Avoid any potential source of heat.

10.5. Incompatible materials

NO CONCERNED

10.6. Hazardous decomposition products

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Dangerous decomposition products: No dangerous decomposition products known.

11. SECTION 11 - TOXICOLOGICAL INFORMATION

11.1. Information on toxicological

LD50 Dermal (rabbit) : **No data**

LD50 oral (rat) : **No data**

12. SECTION 12 - ECOLOGICAL INFORMATION

12.1. Toxicity

Do not leave the product, even diluted or in great quantity, penetrate the ground water, water or the drains.

LC50 Ecotoxicity : **No data**

EC50 Ecology : **No data**

12.2. Persistence and degradability

NO CONCERNED

12.3. Bioaccumulative potential

NO CONCERNED

12.4. Mobility in soil

PNEC sol :

12.5. Results of PBT and vPvB assessment

vPvB :
PBT :

12.6. Other adverse effects

No data

13. SECTION 13 - DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product : Does not have to be evacuated with the refuse. Not let it penetrate in the sewers.

Not cleaned packing : Evacuation according to local reglementation.

Safety Data Sheet

Printed : 25/01/2021

YUZU TYPE

Revised : V1-R-MP-2-CLP from 25/01/2021

14. SECTION 14 - TRANSPORT INFORMATION

ADR:



IMDG:



IATA:



14.1. UN number

ADR : 1169 (Tunnel code (D/E))
IMDG:1169
IATA :1169

14.2. UN proper shipping name

ADR : EXTRACTS, AROMATIC, LIQUID
IMDG:EXTRACTS, AROMATIC, LIQUID
IATA :EXTRACTS, AROMATIC, LIQUID

14.3. Transport hazard class(es)

ADR : 3
IMDG:3
IATA :3

14.4. Packing group

ADR : III
IMDG:III
IATA :III

14.5. Environmental hazards

IMDG :

14.6. Special precautions for user

NO CONCERNED

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

(Except particular case)

IBC Liquid substances
Metal (31A, 31B, 31N)

Safety Data Sheet

Printed : 25/01/2021

YUZU TYPE

Revised : V1-R-MP-2-CLP from 25/01/2021

Plastic (31H1, 31H2)

GRV Solid substances

Metal (11A, 11B, 21A, 21N)

Plastic (11H1, 11H2, 21H1, 21H2)

15. SECTION 15 - REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Monographie (s) du RIFM n° : /

Custom tariff : **3302 90 90 00**

15.2. Chemical safety assessment

16. SECTION 16 - OTHER INFORMATIONS

Full H sentences text in point 3 :

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Key literature references and sources for data

Sources for data : Information from supplier

Literature references : ECHA

Literature references EU : Reg. 1272/2008

Safety data sheet according to REG. 1272/2008/CE and its amendings

These indications are founded on the current state of our knowledge, but do not constitute a guarantee as for the properties of the product and do not give place to a contractual legal report.

Modified points : 14.5