

Printed : 03/05/2024

Revised : CLP V1-R-1-CLP from 03/05/2024

## **BUTYL ACETATE**

## 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY

1.1. Product identifier

## BUTYL ACETATE

N° CAS	: 123-86-4
N° CE	: 204-658-1
N° index REACH An VI	: 607-025-00-1
N° REACH (partially)	: Exempt UE

**IUPAC Name :** 

## n-Butyl acetate

Chemical / REACH name : n-Butyl acetate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use only

End use :

## Fragrances / Cosmetic / Flavours

## 1.3. Details of the supplier of the safety data sheet

Company : PCW 45 Boulevard Marcel PAGNOL Parc Aromagrasse 06130 GRASSE - FRANCE Tel:+33 (0)4 92 42 35 00 Fax :+33 (0)4 92 42 35 19 Web :www.pcwfrance.com Email :info@pcwfrance.com

Technical manager : regulatory@pcwfrance.com

## 1.4. Emergency telephone number

## Emergency information service of the company

+33(6) 07 85 74 60 (24h/24h)

## National emergency information service

INERIS: +33(8) 20 20 18 16

## Anti poison Centers in France

ORFILA : +33(1) 45 42 59 59



Printed :

03/05/2024

**BUTYL ACETATE** 

Revised : CLP V1-R-1-CLP from 03/05/2024

## 2. HAZARDS IDENTIFICATION

## 2.1. Classification of the substance or mixture

GHS Classification :

(RegulationCLP)

 Flam. Liq. 3
 Flammable Liquids 3

 Stot Se 3Ne
 Toxicité organes cibles - expo unique 3 NE

H226 - Flammable liquid and vapour. H336 - Kann Schläfrigkeit und Benommenheit verursachen.

### 2.2. Label elements

GHS Classification :

(RegulationCLP)



Warning mention : Warning

Flam. Liq. 3Flammable Liquids 3Stot Se 3NeToxicité organes cibles - expo unique 3 NE

H226 - Flammable liquid and vapour.

H336 - Kann Schläfrigkeit und Benommenheit verursachen.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240+P241 - Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting/.../equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 - Call a POISON CENTER/doctor/... if you feel unwell.

P501 - Dispose of contents/container according to the local/ regional / national / international Regulation.

## 2.3. Other hazards

The substance/mixture does not contain components considered to have endocrine disrupting properties according to Article 57(f) of REACH or Commission Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0,1 % or more.

#### **Contains Butyl acetate**



Safety Data Sheet			
Printed :	03/05/2024	BUTYL ACETATE	Revised : CLP V1-R-1-CLP from 03/05/2024
PBT :		This substance is not consident nor toxic	dered as persistent, neither bioaccumalable
vPvB:		This substance is not considered as very persistent nor very bioaccumulative	
VOC Swiss - Annex 1 : Listed			

3. COMPOSITION / INFORMATION ON INGREDIENTS

List of reportable components:

#### 3.1. Substances

Numéro d'identification	Substance	Classes danger & Phrases H	LCS / Facteurs M / ATE	Percent %
CAS# 123-86-4 EINECS# 204-658-1 REACH# N° REACH 01-2119485493-29-xx xx / N° INDEX 607-025-00-1	Butyl acetate	Flam. Liq. 3, Stot Se 3Ne H226, H336		> 50 %

The substance/mixture does not contain components considered to have endocrine disrupting properties according to Article 57(f) of REACH or Commission Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0,1 % or more.

### 3.2. Mixtures

Not concerned

## 4. FIRST AID MEASURES

#### 4.1. Description of first aid measures

**General notes:** Please refer to the risk and safety statements (section 2)

**Following inhalation:** If inhaled : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Remove collar, belt, tie... Give artificial respiration if not breathing.

**Following ingestion:** If swallowed: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting.

**Following skin contact:** If on skin (or hair) or clothing rinse immediately contaminated clothing and skin with plenty of water before removing clothes. If the symptom persists, consult a doctor.

**Following eye contact:** Rinse cautiously with water for several minutes (15 minutes open eyelids). Remove contact lenses, if present and easy to do. Continue rinsing. In case of disorder, consult an ophtalmologist.

Self-protection of the first aider: In lack of appropriate formation, none initiative should imply an individual risk.

## 4.2. Most important symptoms and effects, both acute and delayed

See section 2



Printed : 03/05/2024

BUTYL ACETATE

Revised : CLP V1-R-1-CLP from 03/05/2024

## 4.3. Indication of any immediate medical attention and special treatment needed

**Contact with skin:** Wash immediately and abundantly with water and soap. Rinse then with clear water. **Contact with eyes:** Abundant rinsing with water (15 minutes open eyelids) then washing with an occular lotion standard Dacryoserum. In case of disorder, consult an ophtalmologist. **In case of ingestion:** Do not induce vomiting, maintain the patient at rest. If problems persist, consult a doctor. **Soiled clothing:** Withdraw soiled clothing and re-use them only after decontamination.

## 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

**Suitable extinguishing media:** Use an extinguishing agent suitable for the surrounding fire. CO2, powder, foam, specific liquid. Do not inhale the fumes.

Unsuitable extinguishing media: Never use a direct stream of water.

5.2. Special hazards arising from the substance or mixture

## Flammability: The product is not easily flammable

Prevention: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

#### Hazardous combustion products:

Release of poison gases: Monoxide de carbone (CO), Dioxyde de carbon (CO2), Oxyde d'azotes (NOx), Dioxyde de soufre (SO2), Cyanures (CN) ....

Auto-ignition temperature (°C) :

5.3. Advice for firefighters

### Never use a direct water jet.

## Special protective equipment for fire-fighters:

Firefighters should wear appropriate protective equipment and self-contained breathing apparatus with full face mask operating in active pressure mode.

## 6. ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

Call immediately the emergency personnel.

Promote adequate ventilation in the area.

### For non-emergency personnel

Keep them away from the area. Avoid all sources of ignition (spark of flame). Avoid skin/eye contact. Do not inhal vapours.

#### For emergency responders

Use personal protective equipment. In case of accidental spills, wear protective gloves during the handling.



Revised : CLP V1-R-1-CLP from 03/05/2024

## Printed : 03/05/2024

BUTYL ACETATE

### 6.2. Environmental precautions

Avoid the dispersion and flow of the product. Keep away from drains, surface and ground water. Inform the competent authorities if the product enters in ground or surface waters.

### 6.3. Methods and material for containment and cleaning up

#### For containment

The spillage is contained with sand or inert powder. The chemical waste is placed in sealed containers.

#### For cleaning up

The soiled elements (rags, absorbent papiers, filters) are immediately soaked into water. The chemical waste are rapidly treated according to the local reglementation

#### Other informations

Only qualified personnel is allowed to clean up.

#### 6.4. Reference to other sections

See section 8 for personal protective equipment and section 13 for waste treatment.

## 7. HANDLING AND STORAGE

### 7.1. Precautions for safe handling

#### Protective measures:

See section 2.2



#### Measures to prevent fire:

Do not smoke. Do not expose to excessive heat or ignition sources (spark or flame).

#### Measures to prevent aerosol and dust generation:

Maintain adequate ventilation in the area.

#### Measures to protect the environment:

Avoid spreading product and keep it from spilling. Precautions or coming in contact with the ground, waterways, drains and vents.

#### Advice on general occupational hygiene:

Follow the general hygiene rules.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in its original packaging in a cool dry place, away from light.

**Technical measures:** Close the container after use. In case of transferring, reproduce the labelling.

Packaging materials: Preserve only in the container of origin.



Printed :

## Safety Data Sheet

**BUTYL ACETATE** 

Revised : CLP V1-R-1-CLP from 03/05/2024

03/05/2024 Respect the general rules of incompatibility.

Storage :	Store at 25°C max. in tightly sealed original container. Avoid prolonged exposure to light, heat and air.
Storage areas and packaging conditions :	Close carefully any already opened recipient and store it vertically to avoid any flow
Protection against the fire and the explosion :	Keep away from heat/sparks/open flames/hot surfaces No smoking.

## 7.3. Specific end use(s)

Wash hands and any other zone exposed with soap and water before eating, drinking, to smoke and before leaving work.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## 8.1. Control parameters

Measures of technical order: Avoid contact with eyes, skin and closes. Do not ingest. Do not inhale vapors. Use proper personal protective equipment.

Monitoring procedures: If the product contains ingredients with exposure limits, it may be necessary to carry out a follow-up examination of people, the workplace atmosphere or living organisms to determine the effectiveness of ventilation or other control measures or to assess the need for respiratory protective equipment. It is important to refer to the European standard EN 689 on methods for assessing inhalation exposure to chemical agents and to national policy documents on methods for determining hazardous substances.

PNEC Fresh water :	No data
PNEC Fresh water sediment :	No data
PNEC Marine water :	No data
PNEC Marine sediment :	No data
PNEC Soil:	No data
VLEP short term mg/m3 (98/24/CE) :	No data
VLEP (8h) mg/m3 (98/24/CE) :	No data
DNEL - Inhalation :	No data
DNEL - Skin contact :	No data

8.2. Exposure controls

#### Appropriate technical controls :

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure.

## Personal protection measures :

## Personal protection equipment :

- Hand protection: Protection not required.- Eye protection: Protection not required.- Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment.



Printed : 03/05/2024

**BUTYL ACETATE** 

Revised : CLP V1-R-1-CLP from 03/05/2024

- Hand protection: Protection not required.- Eye protection: Protection not required.- Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment.

**Respiratory protection**: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates that is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Filter apparatus (dust masks or half masks)

Type of filters

Type AX (Brown) : Organic compounds boiling point < 65°C

Type A (Brown) : Organic compounds boiling point > 65°C

Type B (Grey) : Inorganic gasses and fumes.

Type P (White) : Particles, dusts and aerosols

**Hand protection** : Impermeable and chemical resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary >8 hours before piercing : vinyle disposable.

**Remark** : The waterproofness of the recommended gloves does not only depend on their material. Also other factors can have an influence on the waterproofness, such as their thickness or specific use or temperature conditions. In any case, material certificates should be selected. Ask your supplier whether the gloves are suitable for this purpose.

**Eyes protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommended : Splash googles, safety glasses with side-shields.

**Skin protection** :Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Body : Recommended : lab coat (sarrau), general.

Type 3 : Liquid impermeability

Type 4 : Aerosol impermeability

Type 6 : Impermeability limited to liquid splashs

Foot : Recommended : neoprene

Upper and sole resistant and impermeable (Hydrocarbure resistant).

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Solubility ethanol :	yes
Appearance :	Liquid
Colour :	Colourless
Odour :	Fruity, pineapple
Refractive index @ 20°C :	[1.389 ; 1.399]
Melting point (°C) :	-
Boiling point (°C) :	126
Flash point (°C) (close cup) :	27
Ignition temperature :	-
Explosive properties :	-
Purity (%) :	[97.0 ; 100.0]
Vapor pressure :	11.500000 mm/Hg @ 25.00 °C (litt)
Partition coefficient n-octanol/water :	LogPow 1.780



## Safety Data Sheet 03/05/2024 Revised : CLP V1-R-1-CLP from 03/05/2024 Printed : **BUTYL ACETATE** 9.2. Other information Water solubility : No **10. STABILITY AND REACTIVITY** 10.1. Reactivity Avoid powerful oxidising agents 10.2. Chemical stability Stable under normal conditions. Shelf life : 24 months, according to storage conditions 10.3. Possibility of hazardous reactions No hazardous reactions when stored and handled according to instructions. 10.4. Conditions to avoid Avoid any potential source of heat. 10.5. Incompatible materials Incompatibility with other materials: Oxydizing non-organic acids, strong reducing agents, strong oxidizing agents Incompatibility with other substances Oxydizing non-organic acids, strong reducing agents, strong oxidizing agents •

## 10.6. Hazardous decomposition products

**Thermal decomposition / conditions to be avoided:** Avoid contact with any flame or spark, flame, Overheat.Avoid Direct rays of the sun. No decomposition if used according to specifications. **Dangerous decomposition products:** No dangerous decomposition products known.

## **11. TOXICOLOGICAL INFORMATION**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Informations Acute :

Orale

No defined

Inhalation

No defined

· Skin



## Safety Data Sheet 03/05/2024 Revised : CLP V1-R-1-CLP from 03/05/2024 Printed : **BUTYL ACETATE** No defined further information: Aucun composant No data Phototoxicity : Genotoxicity in vivo : No data Genotoxicity in vitro : No data LD50 oral (rat) : No data LD50 Dermal (rabbit) : 9000 mg/kg LC50 by inhalation : 21 mg/kg Respiratory or Skin sensitization : No data Skin irritation : No data Serious eye damage/irritation : No data Eyes irritation : No data

11.2. Information on other hazards

The product does not contain substances identified as having endocrine disrupting properties (human health) in concentrations equal to or greater than 0.1% (m/m).

## 12. ECOLOGICAL INFORMATION

## 12.1. Toxicity

Do not leave the product, even diluted or in great quantity, penetrate the ground water, water or the drains.

CE50 (Aquatic fauna) :	44 mg/L - Daphnia magna - 48h
CE50 (Aquatic flora) :	No data
No observable adverse effect level (NOAEL) :	No data
No observed effect level (NOEL) :	No data
12.2. Persistence and de	gradability
Biodegradability :	>70% - 28 days
12.3. Bioaccumulative po	otential
Bioaccumulation (LogPow) :	1.780
12.4. Mobility in soil	



Printed : 03/05/2024

**BUTYL ACETATE** 

Revised : CLP V1-R-1-CLP from 03/05/2024

PNEC soil : No data

### 12.5. Results of PBT and vPvB assessment

vPvB : This substance is not considered as very persistent nor very bioaccumulativePBT : This substance is not considered as persistent, neither bioaccumalable nor toxic

## 12.6. Endocrine disrupting properties

The product does not contain substances identified as having endocrine disrupting properties (environment) in concentrations equal to or greater than 0.1% (m/m).

12.7. Other adverse effects

Not concerned

13. DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Product:** Recommendation: Does not have to be evacuated with the refuse. Do not let penetrate into drains/waste water system.

Not cleaned packing: Recommendation: Evacuation in accordance with the regulations.

## 14. TRANSPORT INFORMATION

ADR/ADN/RID:



IMDG:



IATA:



14.1. UN number or ID number

```
ADR/ADN/RID : 1123 (Tunnel code (D/E) )
IMDG:1123
IATA :1123
```



Printed : 03/05/2024

**BUTYL ACETATE** 

Revised : CLP V1-R-1-CLP from 03/05/2024

14.2. UN proper shipping name

ADR/ADN/RID : BUTYL ACETATES IMDG:BUTYL ACETATES IATA :BUTYL ACETATES

14.3. Transport hazard class(es)

ADR/ADN/RID : 3 IMDG:3 IATA :3

14.4. Packing group

ADR/ADN/RID : III IMDG:III IATA :III

14.5. Environmental hazards

IMDG : Not concerned

14.6. Special precautions for user

Precautions of use :

Avoid any direct contact with the product.

14.7. Maritime transport in bulk according to IMO instruments

(Except particular case)

IBC Liquid substances Metal (31A, 31B, 31N) Plastic (31H1, 31H2)

<u>GRV Solid substances</u> Metal (11A, 11B, 21A, 21N) Plastic (11H1, 11H2, 21H1, 21H2)

## **15. REGULATORY INFORMATION**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

WGK :

Custom tariff :

1 - ID 42 2915 33 00 00

15.2. Chemical safety assessment

Exposure assessment :

16. OTHER INFORMATION

## Full H sentenses text in point 3 :

H226

Flammable liquid and vapour.

\_



Printed : 03/05/2024

BUTYL ACETATE

Revised : CLP V1-R-1-CLP from 03/05/2024

H336 Kann Schläfrigkeit und Benommenheit verursachen.

Material security data sheet according to 2020/878/CEE.

These indications are founded on the current state of our knowledge, but do not constitute a guarantee as for the properties of the product and do not give place to a contractual legal report.

Modified points : 2.1 2.2 2.3 3.1 9.1 10.5 11.1 12.1