

Printed : 11/09/2020

Revised : V1-R-3-CLP from 11/09/2020

MUSK C14

1. SECTION 1 - IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

1.1. Product identifier

| Name of the substance/mixture | : MUSK C14 | |
|--|---|--|
| N° CAS TSCA N° CE N° index REACH An VI N° REACH (partially) | : 54982-83-1 : 259-423-6 : / : 01-2119524000-64-xxxx | |
| IUPAC Name : | 1,4-Dioxacyclohexadecane-5,16-Dione | |
| Chemical / REACH name : | 2,5-dioxacyclohexadecane-1,6-dione | |
| Molecular formula : | C14 H24 O4 | |
| Molecular weight : | 256.4 | |
| 1.2. Relevant identified uses of the substance or mixture and uses advised against | | |

Use of the substance/mixture : Industrial use only

End use :

Fragrances / Cosmetic

1.3. Details of the supplier of the safety data sheet

SAS PCW Aromagrasse - 45 bd Marcel Pagnol 06130 Grasse - FRANCE Tel : +33 (0)4 92 42 35 00 Fax : +33 (0)4 92 42 35 19 Web : www.pcwfrance.com Email : info@pcwfrance.com

Technical manager : regulatory@pcwfrance.com

1.4. Emergency telephone number

Emergency information service of the company

+33(6) 07 85 74 60 (24h/24h)

National emergency information service

INERIS : +33(8) 20 20 18 16

Anti poison Centers in France

ORFILA : +33(1) 45 42 59 59



Printed : 11/09/2020

MUSK C14

Revised : V1-R-3-CLP from 11/09/2020

2. SECTION 2 - HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification :

(RegulationCLP)

Aquatic Acute 1Hazardous to the aquatic environment, acute hazard 1Aquatic Chronic 3Hazardous to the aquatic environment, long-trem hazard 3

H400 - Very toxic to aquatic life.

2.2. Label elements

GHS Classification :

(RegulationCLP)



Warning mention : Warning

Aquatic Acute 1 Hazardous to the aquatic environment, acute hazard 1 Aquatic Chronic 3 Hazardous to the aquatic environment, long-trem hazard 3

H400 - Very toxic to aquatic life.

P501 - Dispose of contents/container according to the local/ regional / national / international Regulation.

2.3. Other hazards

PBT :

This substance is not considered as persistent, neither bioaccumalable nor toxin This substance is not considered as very persistent nor very

 vPvB :
 This substance is not considered as very plication

 VOC Swiss - Annex 1 :
 Non listé

LVP-VOC / INORGANIC / EXEMPTED **100%** VOC (CARB) :

CMR (Reg. 1223/2009/EEC) :

See certificate

3. SECTION 3 - COMPOSITION INFORMATION ON INGREDIENTS

3.1. Substances

| Material | C.A.S | EINECS | Classification | Percent % |
|---|------------|-----------|--|-----------|
| Ethylene dodecanedioate (Regist. : N°REACH 01-2119524000-64-xxxx) | 54982-83-1 | 259-423-6 | Aquatic Acute 1, Aquatic Chronic 3 - H400, H412 | > 50 % |



Printed : 11/09/2020

MUSK C14

Revised : V1-R-3-CLP from 11/09/2020

3.2. Mixtures

NO CONCERNED

4. SECTION 4 - FIRST AID MEASURES

4.1. Description of first aid measures

General notes : Please refer to the risk and safety statements (section 2)

Following inhalation : If inhaled : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Remove collar, belt, tie... Give artificial respiration if not breathing.

Following ingestion : If swallowed: Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting.

Following skin contact : If on skin (or hair) or clothing rinse immediately contaminated clothing and skin with plenty of water

before removing clothes. If the symptom persists, consult a doctor.

Following eye contact : Rinse cautiously with water for several minutes (15 minutes open eyelids). Remove contact lenses, if present and easy to do. Continue rinsing. In case of disorder, consult an ophtalmologist.

Self-protection of the first aider : In lack of appropriate formation, none initiative should imply an individual risk.

4.2. Most important symptoms and effects, both acute and delayed

See section 2

4.3. Indication of any immediate medical attention and special treatment needed

See section 2

5. SECTION 5 - FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire. CO2, powder, foam, specific liquid.

Unsuitable extinguishing media : Never use a direct stream of water.

5.2. Special hazards arising from the substance or mixture

Flammability : The product is not flammable.

Prevention : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Particular risks linked to exposure : see section 2

Hazardous combustion products :

Release of poison gases : Monoxide de carbone (CO), Dioxyde de carbon (CO2), Oxyde d'azotes (NOx), Dioxyde de



Printed : 11/09/2020

MUSK C14

Revised : V1-R-3-CLP from 11/09/2020

soufre (SO2), Cyanures (CN)

Auto-ignition temperature (°C) :

5.3. Advice for firefighters

Fire-fighting equipment : use an appropriate personal protective equipment with an approved positive-pressure self-contained breathing apparatus.

6. SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Call immediately the emergency personnel.

Promote adequate ventilation in the area.

For non-emergency personnel Keep them away from the area. Avoid all sources of ignition (spark of flame). Avoid skin/eye contact. Do not inhal vapours.

For emergency responders Use personal protective equipment. In case of accidental spills, wear protective gloves during the handling.

6.2. Environmental precautions

Avoid the dispersion and flow of the product. Keep away from drains, surface and ground water. Inform the competent authorities if the product enters in ground or surface waters.

6.3. Methods and material for containment and cleaning up

For containment

The spillage is contained with sand or inert powder. The chemical waste is placed in sealed containers.

For cleaning up

The soiled elements (rags, absorbent papiers, filters) are immediately soaked into water. The chemical waste are rapidly treated according to the local reglementation

<u>Other informations</u> Only qualified personnel is allowed to clean up.

6.4. Reference to other sections

See section 8 for personal protective equipment and section 13 for waste treatment.

7. SECTION 7 - HANDLING AND STORAGE

7.1. Precautions for safe handling



Printed : 11/09/2020

MUSK C14

Revised : V1-R-3-CLP from 11/09/2020

Protective measures: See section 2.2



Measures to prevent fire:

Do not smoke. Do not expose to excessive heat or ignition sources (spark or flame).

Measures to prevent aerosol and dust generation: Maintain adequate ventilation in the area.

<u>Measures to protect the environment:</u> Avoid spreading product and keep it from spilling. Precautions or coming in contact with the ground, waterways, drains and vents.

Advice on general occupational hygiene: Follow the general hygiene rules.

Precautions of use : No data

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in its original packaging in a cool dry place, away from light.

<u>Technical measures:</u> Close the container after use. In case of transferring, reproduce the labelling.

Packaging materials: Preserve only in the container of origin.

Respect the general rules of incompatibility.

| Storage : | Store in cool place (10°C max.), in tightly sealed original container. Avoid prolonged exposure to light, heat and air. |
|---|--|
| Storage areas and packaging conditions : | Close carefully any already opened recipient and store it vertically to avoid any flow |
| Protection against the fire and the explosion : | Non-flammable |

7.3. Specific end use(s)

Wash the hands and any other zone exposed with soap and water before eating, drinking, to smoke and before leaving work.

8. SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Measures of technical order : Avoid contact with eyes, skin and closes. Do not ingest. Do not inhal vapors. Use proper personal protective equipment.

Monitoring procedures : If the product contains ingredients presenting exposure limits, he can turn out necessary to make an examination followed by the persons, by the atmosphere in the workplace either bodies living to end the efficiency of the ventilation or the other control measures or estimate the need to use of the material of protection of respiratory tracts. It is important to put back you in the European standard EN 689 concerning the methods to estimate the exhibition by inhalation to the chemical agents and to the national general documents of politics relative to the



Printed :

Safety Data Sheet

Revised : V1-R-3-CLP from 11/09/2020

methods to determine dangerous substances.

11/09/2020

| PNEC Fresh water : | 0.00088 mg/l |
|------------------------------------|--|
| PNEC Fresh water sediment : | 0.162 mg/kg |
| PNEC Marine water : | 0.000088 mg/l |
| PNEC Marine sediment : | 0.0162 mg/kg |
| PNEC Soil: | 0.0318 mg/kg |
| VLEP short term mg/m3 (98/24/CE) : | No data |
| VLEP (8h) mg/m3 (98/24/CE) : | No data |
| DNEL - Inhalation : | End Use : Workers - Potential health effects : Chronic effects - Exposure time : 8h - Value : 182 mg/m3 |
| DNEL - Skin contact : | End Use : Workers - Potential health effects : Chronic effects - Exposure time : 8h - Value : 25.8 mg/kg bw/day |

MUSK C14

8.2. Exposure controls

Appropriate technical controls :

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure.

Personal protection measures :

Personal protection :

-Protection des mains : Protection non requise.-Protection des yeux : Protection non requise.

-Protection respiratoire : En cas de ventilation insuffisante, porter un appareil respiratoire approprié.

Respiratory protection: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates that is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Filter apparatus (dust masks or half masks)

Type of filters

Type AX (Brown) : Organic compounds boiling point < 65°C

Type A (Brown) : Organic compounds boiling point > 65°C

Type B (Grey) : Inorganic gasses and fumes.

Type P (White) : Particles, dusts and aerosols

Hand protection : Impermeable and chemical resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary >8 hours before piercing : vinyle disposable.

Remark: Recommended impermeable goggles do not only depend of his matter. Other factors can have a signifiant effect on impermeability, like their thickness or specific use or temperature conditions. In all cases, matter certificates should be selected. Ask your supply if the goggles are appropriate to this use.

Eyes protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommanded : Splash googles, safety glasses with side-shields.

Skin protection :Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Body : Recommanded : lab coat (sarrau), general.

Type 3 : Liquid impermeability

Type 4 : Aerosol impermeability

Type 6 : Impermeability limited to liquid splashs

Foot : Recommanded : neoprene

Upper and sole resistant and impermeable (Hydrocarbure resistant).



Printed : 11/09/2020

MUSK C14

Revised : V1-R-3-CLP from 11/09/2020

Upper and sole resistant and impermeable (Hydrocarbure resistant).

9. SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

| Appearance : | Liquid |
|---|--------------------------|
| Color : | Colorless to pale yellow |
| Odour : | Animal, Musky |
| Density at 20°C : | [1.049 ; 1.063] |
| Refractive index @ 20°C : | [1.465 ; 1.473] |
| Acid Value : | < 1.0 mgKOH/g |
| Melting point (°C) : | 16.72 |
| Boiling point (°C) : | 337.3 |
| Flash point (°C) (close cup) : | 166 |
| Ignition temperature : | 385 |
| Explosive properties : | - |
| Purity (%) : | > 98.0% |
| Impurities >0.01% : | - |
| Vapor pressure : | 0.028 Pa |
| Partition coefficient n-octanol/water : | log Pow 3.65 |
| Viscosity : | 0.097 mPa.s @ 20°C |
| 9.2. Other information | |

Water solubility :

Solubility in alcohol (°) : 75%

10. SECTION 10 - STABILITY AND REACTIVITY

No

10.1. Reactivity

Avoid powerful oxidizing agents

10.2. Chemical stability

Stable under normal conditions.

Shelf life :

24 months, according to storage conditions

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid



Revised : V1-R-3-CLP from 11/09/2020

Printed : 11/09/2020

MUSK C14

Avoid any potential source of heat.

10.5. Incompatible materials

NO CONCERNED

10.6. Hazardous decomposition products

Thermal decomposition / **conditions to be avoided:** No decomposition if used according to specifications. **Dangerous decomposition products:** No dangerous decomposition products known.

11. SECTION 11 - TOXICOLOGICAL INFORMATION

11.1. Information on toxicological

| Phototoxicity : | No data |
|-------------------------------------|---|
| Genotoxicity in vivo : | No data |
| Genotoxicity in vitro : | No data |
| LD50 oral (rat) : | 4500 mg/kg |
| LD50 Dermal (rabbit) : | >5000 mg/kg (litt.) |
| Respiratory or Skin sensitization : | (guinea pig) : Cause no sensitization (litt.) |
| Skin irritation : | (Rabbit) : No skin irritation (litt.) |
| Serious eye damage/irritation : | No data |
| Eyes irritation : | (Rabbit) : No eye irritation (litt.) |

12. SECTION 12 - ECOLOGICAL INFORMATION

12.1. Toxicity

Do not leave the product, even diluted or in great quantity, penetrate the ground water, water or the drains.

| LC50 Ecotoxicity : | 0.88 mg/L, 96h, fish | |
|---|-------------------------|--|
| EC50 Ecology : | No data | |
| CE50 (Aquatic fauna) : | > 14 mg/L, 48h, Daphnia | |
| CE50 (Aquatic flora) : | 17 mg/L, 72h, Algae | |
| No observable adverse effect level (NOAEL) : | No data | |
| No observed effect level (NOEL) : | No data | |
| 12.2. Persistence and degradability | | |
| Biodogradability : | Peadily biodegradable | |

Biodegradability : Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation (LogPow) : 3.65

12.4. Mobility in soil

PNEC sol : 0.0318 mg/kg



11/09/2020 Printed :

MUSK C14

Revised : V1-R-3-CLP from 11/09/2020

12.5. Results of PBT and vPvB assessment

vPvB : This substance is not considered as very persistent nor very bioaccumulative PBT

: This substance is not considered as persistent, neither bioaccumalable nor toxin

12.6. Other adverse effects

No data

13. SECTION 13 - DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product : Does not have to be evacuated with the refuse. Not let it penetrate in the sewers. Not cleaned packing : Evacuation according to local reglementation.

14. SECTION 14 - TRANSPORT INFORMATION

ADR:



IMDG:



IATA:



14.1. UN number

ADR: 3082 (Tunnel code (E)) IMDG:3082 IATA: 3082

14.2. UN proper shipping name

ADR : Environmentally hazardous substance, liquid, n.o.s., (Ethylene dodecanedioate) IMDG:Environmentally hazardous substance, liquid, n.o.s., (Ethylene dodecanedioate) IATA :Environmentally hazardous substance, liquid, n.o.s.,(Ethylene dodecanedioate)

14.3. Transport hazard class(es)

ADR : 9 IMDG:9



Printed : 11/09/2020

MUSK C14

Revised : V1-R-3-CLP from 11/09/2020

IATA :9

14.4. Packing group

adr : III Imdg:III Iata :III

14.5. Environmental hazards

IMDG :

14.6. Special precautions for user

No data

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

(Except particular case)

IBC Liquid substances Metal (31A, 31B, 31N) Plastic (31H1, 31H2)

<u>GRV Solid substances</u> Metal (11A, 11B, 21A, 21N) Plastic (11H1, 11H2, 21H1, 21H2)

15. SECTION 15 - REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

WGK :

2-ID3383

Custom tariff : 2932 20 90 90

15.2. Chemical safety assessment

Exposure assessment :

16. SECTION 16 - OTHER INFORMATIONS

Full H sentenses text in point 3 :

H400 Very toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Key literature references and sources for dataSources for data :Information from supplierLiterature references :ECHALiterature references EU :Reg. 1272/2008

Safety data sheet according to REG. 1272/2008/CE and its amendings These indications are founded on the current state of our knowledge, but do not constitute a guarantee as for the properties of the product and do not give place to a contractual legal report.

Modified points : 11.1